

BACKGROUND

Surface Fasteners of the Slidingly Engagable type (SEFs) were disclosed in US 5,983,467 entitled "Interlocking Device" by the undersigned. That disclosure included a range of fastener types, each including portions with a base structure having pluralities of apertures and islands, which may be slidingly engaged by application of a relative shearing force, so that the individual islands of one portion become interlocked within complementary apertures of the other, and vice versa. SEFs may be provided in various designs including uni-directional or multi-directional orientations; may be hermaphroditic or have different male and female portions; may be configured to connect a point, an edge, a strap, a surface or other condition; may include an associated aperture opening that provides a "snap fit" prior to engagement; and may also include diverse self-alignment and coupling mechanisms.

Typically, the individual apertures of Slidingly Engagable Fasteners are designed to receive complementary islands so as to allow a relatively loose and imprecise initial alignment to result in a relatively tight and more precise engaged state, after application of a relative shearing force. Three characteristics define this aspect. First, the apertures and complementary islands are effectively tapered in at least one dimension in relation to the axis of engagement so as to provide an aperture opening that is somewhat larger in at least one dimension than the leading edge of an associated island, thereby abetting self-alignment of the elements. Secondly, each such aperture includes at least one undercut wall segment which, after application of the relative shearing force (i.e. a force applied to one of the portions in a direction generally parallel with the basal surface) to the aligned portions, engages a complementary island undercut sidewall segment so as to contain the island and prevent further movement in a direction generally perpendicular to the basal surface (vertical). Thirdly, each such aperture also includes wall segments which, upon application of the relative shearing force, engage complementary island sidewall segments so as to contain such island and prevent further movement in the direction of such applied shearing force (engagement direction) or in a direction generally perpendicular to such force and also parallel with the basal surface (lateral direction).

The term "slidingly engaged" is intended to convey that the islands are caused (by the relative shearing force) to enter complementary apertures so that the island sidewalls progressively approach aperture walls until reaching a state of full contact and engagement, in which state the portions are effectively interlocked.

The profile shape of such walls and sidewalls (as viewed in cross section perpendicular to the axis of engagement), as illustrated in US 5,983,467 include orthogonal dovetail-like shapes, ogee-like shapes, and variations of such shapes. It is apparent that any profile shape which provides the appropriate engagement and containment aspects as described above may be used. It may also be understood that any such walls or sidewalls need not be contiguous in order to provide such engagement and containment aspects. Therefore it has become known to the present inventor that Slidingly Engagable Fasteners may include elements which are discontinuous, perforated, or otherwise modified in design, provided only that the essential function and structural integrity of the device is maintained. In that a basic engineering design precept entails minimizing resources in order to achieve a particular function, it may therefore be desirable to produce Improved SEFs with such discontinuity, perforations or other modifications in order to minimize such resources.

SEFs can provide significant advantages over hook-and-loop, mushroom-type and other surface fasteners, as well as a wide variety of mechanical fastening devices, for many applications. Such advantages include superior shear and tensile strength, low profile, ease of use, durability, a non-grabbing texture, and numerous other aspects. However, in order to advantageously provide these advantages, a simple and economical method of producing SEF fasteners in large or small quantities, in a variety of materials, and in a range of designs is needed.

In addition to the need for an improved method of production, a number of potential improvements to such fasteners are also desirable which may also be related to such method of production. Slidingly Engagable Fasteners should be available in a variety of materials including molded thermoplastics, other moldable materials, paper and paper

board, composite and fibrous materials, and in formed metals, plastics and other malleable materials. Flexibility of the overall structure should be combined with structural integrity of individual fastening elements. SEF products should be available in a range of scales for a diversity of applications. Use and disposition of materials should be economical. Low profile and high strength aspects should be maximized. Fastener portions for many potential application environments should be self-cleaning. Self connecting fasteners in strap or linear forms should be available, including double-sided fastener straps and surfaces. Provisions for integrally attaching SEFs to various substrates should be available. SEF portions which may be integrally molded or formed as part of a larger component or product are also needed. Fasteners which combine certain of these aspects as well as other features are also needed.

Working prototypes of SEFs in various embodiments have been produced by molding, machining, forming, constructing, and die cutting diverse materials such as hard and soft plastics, wood, paper and paperboard, foam, sheet metal, ceramic materials, and composite materials. Although these models have generally been functionally successful, the need for a simple and inexpensive method of production is apparent. Molding or forming SEF fastener portions by conventional methods is complicated by the fact that such fasteners include a multiplicity of undercut surfaces. Although conventional molding or forming techniques may be employed to produce various uni-directional SEFs, multi-directional embodiments present a particular challenge. Therefore, a relatively simple method is needed which will provide for the removal of that part of the die or mold which defines the underside of such undercut surfaces without harming, weakening, or compromising the design of the product.

Several known manufacturing processes are applicable to the present invention: injection molding utilizing a reciprocating machine; continuous molding in which a substance is molded between a set of counter rotating rollers, effectively extruding a continuous product; die forming utilizing a reciprocating press; and continuous die forming in which a sheet of material is formed between a set of rotating dies. Each of these processes has been developed extensively over many years, and are not claimed herein except in

relation to the present invention. Each such process also involves numerous secondary systems for pressurizing, heating, cooling, lubricating, ejecting product and waste, and other considerations which are beyond the scope of this disclosure. The common aspects of these processes are that each utilize a set of dies or, more commonly, a single die with a corresponding anvil or backing, and an apparatus designed to provide pressure on a raw material in order to produce a product of the desired shape.

Reclosable surface fasteners such as molded hook-and-loop hookstrips and mushroom type fasteners, which also include undercut surface segments, are typically manufactured of molded thermoplastics. Erb US 3,147,528 describes a method of producing hookstrips by reciprocal injection molding. Other methods utilize a continuous web process using a belt or rotary mold. Undercut fastening elements may be formed by a complex mold with internally moving elements i.e. Menzin et al US 3,758,657; they may be directly molded in cavities provided in such a mold and rapidly cooled before forcibly (resiliently) stripping from the mold i.e. Fischer 4,775,310; or they may be formed in a two step process in which a base with an array of stems is first molded and the stems are subsequently reformed into hooks or mushroom shapes, i.e. Provost et al US 5,953,797. Yet another possible manufacturing method includes a sacrificial mold portion for forming undercuts, i.e. Torigoe et al US 5,242,649. Recently, Kampfer et al US 6,000,160, Miller 6,054,091, and Parellada et al US 6,248,276, each disclose improved methods of forming fastener elements by the aforementioned two step process. Many other examples provide variations and refinements to similar processes. It appears that the quest for a definitive method of manufacturing fastener products is ongoing.

Utilizing a set of interengaging dies is a known method of manufacturing complex products with under-surfaces, most commonly known in paper and sheet metal stamping at least as far back as Hodgson US 299,982 of 1884, but also employed in plastic molding. Methods of producing certain designs of hook-and-loop hookstrips and mushroom type fasteners by utilizing an apparatus which includes a set of bypassing dies are also known. Kaneko US 5,212,853 discloses injection molded surface fastener products that utilize a set of male and female interdigitating dies to form a unique mushroom-type fastener portion, although such method is not claimed. Kaneko's

product includes a fastener head on two legs which are flush with the head perimeter, apparently to provide flexibility. His method includes a set of male and female dies with abutment faces, such faces being more or less perpendicular to the product surface structure. Although it is noted that the abutment faces are slightly tapered to facilitate die separation, it would appear that, without further remedy, repetitive use under heat and pressure could cause die seizure or differential movement if anything other than small portions are produced. Like other types of mushroom fasteners, Kaneko's device appears to be limited in potential strength as related to durability under repetitive use. Kayaki US 5,067,210 appears to depend on a similar molding method which is not described. His device appears to require relatively exact positioning in two dimensions, first to align the ribs then to align alternately offset elements. It is apparent that each such fastener has limited application.

Certain other known fasteners also include a fenestrated base structure which could be produced by a method incorporating bypassing dies. Spier, US 4,581,792, describes a press-together surface fastener comprising a plurality of perpendicular tapered projections and complementary receptacles arrayed in alternating rows each surrounded by a contiguous base structure having openings at each such projection and receptacle. Spier's device, however, appears to maintain engagement by friction rather than providing any type of interlock. It requires precise alignment of the portions, and does not appear to provide significant resistance to shear. Cousins, US 4,183,121, and Allan, US 5,640,744, each disclose types of surface fasteners with undercut elements which include portions having a fenestrated base structure, an engagement mechanism which may be effected by a relative shearing force, and in which openings in the fenestrated base structure at least partially align with undersurface segments of individual engagement members. However, each of these fastening devices appear to require considerable precision in aligning the elements both lineally in columns and in angular orientation. The former, Cousins, appears to require consistent pressure along the length of its axis in order to engage all elements simultaneously, and does not provide for excess overlap when adjusted. The latter, Allan, also requires longitudinal alignment ribs to prevent lateral disengagement. Both provide fastening mechanisms which are not

adaptable to resist shear forces oriented in more than a single radial direction and have other limitations.

A new manufacturing method for SEFs should include certain desirable aspects. For instance, having a positive means of defining the thickness of a fastener portion throughout its area is particularly important for producing wide products with either reciprocating or rotating molding systems. Provisions for maximizing production speed are also desirable. Providing enhanced surface features for functional, aesthetic, or identification purposes is also desirable. Precise definition of the shape of individual fastening elements is important in controlling the design of strength and release characteristics. Material efficiency, weight, and flexibility should be carefully designed. Strength of individual fastening elements and profile depth require precise control. Speed, simplicity, and economy of production are important considerations as well are tooling costs. Provision of a method by which fastener portions may be readily manufactured in a one-step process as part of a larger primary product would also have significant utility. In summary, there is a need for a simple, efficient, economical, precise, and versatile method of manufacturing Slidingly Engagable Fastening products.

SUMMARY OF DRAWINGS

Fig. 1 Perspective view of a portion of an improved fastener of the Slidingly Engagable type (SEF) having multi-directional orientation and a quadrille configuration.

Fig. 2 Perspective view of an improved SEF portion having multi-directional orientation and a triangular configuration

Fig. 3 Perspective view of an improved SEF portion having multi-directional orientation and a hexagonal configuration

Fig. 4 Perspective view of an improved SEF portion having a uni-directional orientation and triangular configuration

Fig. 5 Perspective view of an improved SEF portion having a uni-directional orientation and a stepped profile

Fig. 6 Perspective view of improved SEF portions having a uni-directional orientation and chevron-like configuration, also having two fastening sides

Fig. 7 Perspective view of an improved SEF portion with multi-directional orientation and triangular configuration, also having two fastening sides.

Fig. 8 Expanded perspective view showing the underside of an embodiment with a provision for attachment to a substrate, including sectional view of completed assembly

Fig. 9 Sectional view of an embodiment with an alternative provision for attachment

Fig. 10 Perspective view of a product incorporating SEF portions as an integral part.

Fig. 11 Schematic perspective illustrating portions of two dies designed to produce a multi-directional SEF portion

Fig. 12 Schematic perspective illustrating portions of two dies designed to produce a uni-directional SEF portion

Fig. 13 Schematic sectional view illustrating portions of two dies designed to produce a product incorporating two SEF portions

Fig. 14 Schematic sectional view illustrating portions of two dies designed to produce a double sided SEF portion

Fig. 15 Schematically illustrates in sectional view a reciprocating molding apparatus which includes a die set

Fig. 16 Schematically illustrates in sectional view a reciprocating cutting/bending apparatus including a die set

Fig. 17 Schematically illustrates in sectional view a rotating cutting/bending apparatus including a die set

Fig. 18 Schematically illustrates in sectional view a continuous molding apparatus including rotating molds incorporating a die set

SUMMARY OF THE INVENTION

A first object of this invention is to provide Improved Slidingly Engagable Fasteners which can be produced inexpensively in large volume. A second object is to provide a method of economically producing such SEFs of diverse moldable or malleable materials. A further object is to provide such fasteners which are efficient in material usage. A further object is to provide such fasteners which are strong and flexible. A further object is to provide such fasteners in diverse configurations and designs. A further object is to provide such fasteners which include provisions for attachment to a substrate. A further object is to provide such fasteners which have two active sides. A further object is to provide such fasteners which include provision for extracting extraneous matter as they are engaged. A further object is to provide a method of manufacturing any such fasteners as an integral part of a larger manufactured product or product component.

The Improved SEFs disclosed herein include complementary portions each comprising: 1) a fenestrated common base structure having a plurality of fenestrations; 2) a plurality of islands each having at least one stem segment with walls, one or more undercut segments with undersides, and a top with an edge; and 3) a plurality of apertures defined by parts of island walls and parts of undersides of island undercut segments. At least a portion of the fenestrations in the common base structure are correspondent, in a direction generally perpendicular to the plane of the base structure, with corresponding undersides of the islands, and the solid segments of such base structure are generally contiguous with the stem portions of such islands. Each embodiment is designed to be slidingly engagable with a complementary portion upon application of a relative shearing force. The fenestrated base structure may also include larger fenestrations as well as other openings or surface features designed for functional or aesthetic effect.

Embodiments include examples of several types of Improved SEF: a multi-directional SEF arrayed in a quadrille pattern which aligns portions at 90 degree radial intervals and provides resistance to shear stresses of any orientation; a multi-directional portion arrayed in an alternating triangular pattern which aligns portions at 120-degree radial

law
PB

intervals and also provides multi directional shear resistance; a multi-directional portion arrayed in a hexagonal pattern which aligns portions at 60 degree radial intervals and provides multi-directional shear resistance; a uni-directional portion with islands and apertures arrayed in a triangular pattern; a double-sided embodiment which includes two active fastening faces on opposite sides of a common base structure thereby allowing the portion to be attached to separate complementary portions or to be doubled back and attached to itself at another location; a double-sided embodiment having a chevron configuration which provides uni-directional connection to portions on opposite sides; and an example of a product of which such improved fasteners are an integral part. Each of these embodiments are intended to schematically illustrate a range of design options and aspects which generally can be mixed or substituted within the scope of the invention. Embodiments include SEF portions which are molded and have differential profile thickness as well as other embodiments having a relatively consistent profile thickness which may be either molded or formed of a sheet material. Any of the embodiments illustrated can be molded or formed integrally with a primary product or component.

Mechanisms for attaching Improved SEF's to a substrate are also provided. These include: a backing portion having an array of pins designed to penetrate through a perforated substrate and engage with complementary receptors opening to the back side of an improved SEF portion; and an Improved SEF portion having an array of attachment devices projecting from its back side which are designed to penetrate and attach to a substrate. Improved SEFs may also be attached to a substrate by conventional means such as sewing or adhesives.

A method of manufacturing such fastener portions is also provided which incorporates an apparatus that includes a set of interengaging dies to effect a cavity which defines the shape of the resultant product. Each such die includes surface segments which are cavity walls, other surface segments which engage complementary segments of the corresponding die so as to define fenestrations in the resultant product, and associated aspects which are common to known molding or forming technology. The apparatus

causes these dies to align and intermesh under sufficient pressure to cause a moldable or malleable material inserted therein to take the shape of the cavity as defined by the cavity walls. Because no portion of the dies are entrapped by any portion of the resultant product, the dies may be readily separated without stressing the undercut portion of fastener elements, and therefore the resultant product design is not limited by the difficulty of molding or forming such undercut portions, and the production process can be expedited.

This method differs distinctly from the common methods of manufacturing other types of surface fastener portions in that both the first and second dies include male and female elements and both may include surfaces which engage with corresponding surfaces of each other in interfacing positions which may be both perpendicular and normal to the common die axis, thereby defining fenestrations in the resultant product. Such fenestrations are aligned at least in part with the undersurfaces of undercut fastener islands thereby defining at least part of the walls of the apertures. The subject method also provides a mechanism for precisely controlling the thickness of molded fastener products in that the engaging surface segments of corresponding dies may be designed to define a specific cavity depth.

The associated apparatus may be of a type designed for molding a resinous or otherwise moldable substance, or the method may be used in conjunction with an apparatus designed as a cutting/bending press to form a malleable substance such as sheet metal or paper board. Such apparatus may be of a reciprocating type, such as an injection molding machine or reciprocating press, or it may be of a continuous production rotary type wherein the dies are arrayed along the surfaces of counter-rotating rollers or molding belts. Although the subject dies are typically to be designed for a specific product, material, and manufacturing technology related to the type of apparatus used, the common method is applicable to each such technology. Whichever apparatus is incorporated, it typically includes numerous basic elements commonly known to industry including means for: engaging the dies in their aligned position; applying pressure as necessary; inserting raw material; ejecting the finished product; and providing for

heating, cooling, lubrication and other subsidiary parts of the process which are not claimed herein.

A significant improvement provided by the present invention is inclusion of the aforementioned fenestrated base structure. This aspect allows such Improved Fasteners to be manufactured economically of diverse materials by the method provided. The fenestrated base also provides for efficient utilization of material, enhances flexibility, provides a means for extracting foreign matter from the fastener assemblage, allows double-sided portions to be produced, allows a fastener portion to be molded or formed as part of a larger product, and provides other advantages which are apparent herein. The fenestrated base can also be designed to enhance the functions of diverting portions into self-alignment and coupling of the portions.

The Improved SEFs also provide significant other advantages including features that enhance usability for many applications. Very low profile, high strength fasteners may be produced because the effective engagement thickness may be as little as only two times the thickness of the material selected. A variety of designs can provide optional configurations and orientations, strength characteristics, functional, and aesthetic aspects. Fastener products can be reinforced or embellished by the inclusion of a reinforcing material. Flexible portions may be furnished in rolled form for shipment and installation. Double-sided SEF portions allow a greater range of application possibilities. Provision of self attachment mechanisms greatly increase the utility of SEF's for many applications and allow fastener portions to be subsequently attached to an end product by an original equipment manufacturer at another site. Provision of such a simple method of production allows fastener portions to be integrally molded or formed with a primary molded or formed product or assembly component, thereby providing such benefits as reduced assembly time and production cost, as well as improved integrated product designs.

Some of the significant advantages of producing fasteners by the method of this invention include the following: The production system is simple and economical and can be readily adopted to commonly known manufacturing systems. Molds of reciprocating or roller type may be produced by commonly known modern machining methods at lower

cost than complex multipart molds. Material utilization can be optimized by designing the fenestrated product base in relation to the expected loading, and lower cost materials may be utilized where appropriate. A high degree of precision can be incorporated in the resultant product. Resultant fastener products can have a reasonable degree of flexibility due to the fenestrated base, even when manufactured of a fairly rigid material in order to maximize strength. Product design is not limited by mold release considerations.

Because the product undersides may be precisely formed or molded, the strength and release characteristics of resultant fastener products may be designed precisely. Fastener products can be rapidly and economically produced in large quantities, or fastener portions can be integrally manufactured as part of a larger molded or formed product.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
22

DESCRIPTION

Fig. 1A schematically illustrates a one portion of a first preferred embodiment 01, an Improved Slidingly Engagable Fastener of a quadrille design which includes two substantially identical such portions designed to fasten and interlock with each other upon application of a relative shearing force. Each such portion includes a base 02 with a first basal surface 15 and a plurality of undercut segments 09 which are spaced from the basal surface. At least the second such portion also includes a base 02 with a basal surface 15 having a plurality of fenestrations 03, and also includes a plurality of stems 07 each with a first end attached to the base and extending away from the base and attached to an undercut segment 09 which in turn extends away from the stem so as to effectively provide an undercut island 04 with at least one underside 10 spaced away from said basal surface. Such a configuration therefore provides at least one aperture 11 which is defined by the undersides 10 of two adjacent islands and the stems 07 which connect the islands with said base in such a spaced disposition.

Each portion 01 may also include a plurality of said islands 04, each having a top surface 05 with an associated edge 06, a stem segment 07 with sidewalls 08, and undercut segments 09 with undersides 10, wherein said edge and said undersides are also sidewalls, and further wherein said undersides are aligned, in a direction generally perpendicular to the plane of said common base structure, with at least portions of said perforations. It should be noted that in this and other embodiments, said stems 07 are generally located between said undercut segments, and vice versa so as to effect an island having a top surface 05 with a segmented edge 06. A plurality of apertures 11 may also be included in said portion 01, each said aperture having an associated aperture opening 12, and walls 13: wherein said aperture opening is defined by said associated edge 06 of each adjacent island 04, and wherein segments of said walls are coincident with segments of said sidewalls 08 and other segments of said walls are coincident with segments of said undersides 10. The portions are designed so that ones of said apertures receive ones of said islands so that, when two such portions are aligned (i.e. ones of islands are inserted through corresponding aperture openings) and are slidingly engaged

by a relative shearing force, said first and second portions become connected and interlocked. Such interlocked portions may subsequently be disconnected by reversing said relative shearing force or, when the base of at least one portion is sufficiently flexible, the portions may be sequentially peeled apart.

Said first preferred embodiment 01 also, optionally, includes a plurality of conical protrusions 14 at the center of each said top surface of each said island, and as said fenestrated base has a first surface 15 between said perforations, said surface including in this design a complementary ridge 16, so that when the tops of the islands of two said portions are caused to contact by application of a perpendicular pressure, said conical protrusions divert the islands towards adjacent aperture openings 12. Therefore, an imprecise initial alignment of the portions results in alignment at the nearest 90 degree radial interval. Thereafter, as ones of said islands are inserted through said aperture openings 12 and caused to contact ones of said ridges 16 on said first face 15, continuing perpendicular pressure causes ones of said protrusions 14 to divert toward said perforations 03 in said common base structure 02, thereby initiating engagement of the portions by effecting a relative shearing force. This type of embodiment, having a quadrille design, allows fastener portions to be aligned and slidingly engaged at 90 degree radial intervals and thence provides resistance to shearing stresses in multiple directions in that, when subjected to a shear stress of a different direction, said islands tend to relocate and engage with whichever aperture is most closely aligned with such shear stress.

Embodiments of the type 01 illustrated in Fig. 1 are designed to be manufactured of a moldable material utilizing a method incorporating a set of interengaging dies associated with an apparatus which is described below. Therefore, this type of embodiment may include a variable cross-sectional dimension, whereas other types of embodiments, as seen below, may have a relatively consistent cross-sectional dimension and therefore may be manufactured of either a moldable material or of a malleable material by utilizing such method with dies and apparatus of an appropriate design. Such molded embodiments may also include an optional integrally molded reinforcement 48.

Ins
AB


A second type of preferred embodiment 20, as illustrated in Fig. 2, also includes a fastener portion having a fenestrated common base structure 02 with a plurality of perforations 03; islands 04 each having a top surface 05 with an associated edge 06, undercut segments 09 with undersides 10, and a plurality of stem segments 07 with sidewalls 08; and a plurality of apertures 11 each having an associated aperture opening 12, and walls 13 which are coincident with segments of said sidewalls 08 and of said undersides 10 as in the embodiment described above, and is designed to slidingly engage with a similar portion when a relative shearing force is applied. This embodiment is configured so that said top surfaces of said islands and said aperture openings are of a generally triangular configuration arrayed in alternately offset rows, thereby allowing portions to be aligned and engaged at substantially 120 degree radial intervals. An advantage of such a triangulated design is that for many applications such as adjustable straps it provides a readily apparent visual key as to the intended directionality of engagement.

In this type of embodiment 20, each said island 04 has a plurality of said stems 07, and said islands and said common base structure 02 have a generally consistent thickness, so that such a portion may be produced either by molding a moldable substance as in the previously described embodiment or by perforating and forming a malleable sheet material utilizing said method incorporating said interengaging dies and said apparatus.

A third preferred embodiment 21, illustrated in Fig. 3, also includes a fenestrated base structure 02 with perforations 03, islands 04, complementary apertures 11 and other aspects as in the previous embodiments. This embodiment, however, is configured in a hexagonal design with islands having a generally hexagonal shape arrayed in offset rows and columns so as to define a multiplicity of apertures associated with each island at 60 degree radial intervals thereby allowing engagement of two portions of such an embodiment at such 60 degree radial intervals. Each island 04 therefore corresponds with six aperture openings 12 defined by adjacent sets of three such islands, whereas each of three undercut segments 09 is included between each of three stem segments 07.

It is apparent that multi-directional embodiments such as this could also include additional divisions of stem and undercut segments, for instance the present embodiment could alternatively include six stems and corresponding undercut segments, etc.

This embodiment 21 also includes island top surfaces having a conical protrusion 14 which is designed to help align and couple said portions. As in the previous embodiment 01, when two such portions are approximately aligned and subjected to compressive pressure, ones of said conical protrusions cause complementary sets of said islands to slide into alignment with said aperture openings so that continuing pressure causes ones of said islands to enter ones of said aperture openings. In this instance, however, the conical protrusions 14 may then be diverted into a corresponding cavity 28 on the basal surface by a relatively slight initial relative shearing force, thereby coupling said portions in an engaged state until an opposing relative shearing force is applied to reverse such engagement. An important aspect of such a hexagonal design combined with such conical protrusions is that two such fastener portions may be pressed together at virtually any radial disposition and will thence self-align at the nearest 60 degree disposition, so long as at least one portion is allowed to rotate up to 30 degrees. Therefore a press-together fastener is provided which may be connected from any initial angular disposition of the portions.

*Ins
As*  A fourth preferred embodiment, illustrated in Fig. 4, includes an improved slidingly engagable fastener portion 23 having a plurality of triangular islands arrayed in offset rows so as to provide a uni-directionally oriented, longitudinally adjustable fastener. As in the embodiments described above, each portion includes pluralities of islands 04 and complementary apertures 11 associated with a fenestrated common base structure 02. In this type of embodiment 23, each of said islands includes stem segments 07 with sidewalls 08 and also includes undercut segments 09 with undersides, said stem segments and undercut segments being configured so as to define one of said apertures 11 between each pair of adjacent islands designed to receive and engage one island in a directionally opposite orientation. One of each of said stem segments 07 of each said island 04 of this embodiment also provides a stopping wall 25 which is designed to prevent ones of said

islands from inadvertently being removed from a pre-engaged disposition when an assembly of said portions is subjected to flexure or to a reversal of said relative shearing force, unless a perpendicular peeling force is also applied. Therefore said fastener portion 23 is designed to primarily resist-shear stresses oriented in a single direction and will also resist inadvertent release when said shear stresses are reduced or absent, unless such a perpendicular peeling force is also applied. Such uni-directional-fasteners may be designed to provide superior shear and tensile (vertical) strength for applications where only uni-directional stresses are expected, and also to provide relative ease of release by peeling.

A fifth preferred embodiment 25, illustrated in Fig. 5, includes a plurality of islands 04 configured in a uni-directional orientation in which said islands are contiguous with a common fenestrated base structure 02, said fenestrated base structure being stepped in profile at each alternate row of said islands so as to provide apertures between such islands. Said islands and apertures are arrayed in rows so that a first surface 15 of said common base structure 02 in a first row is substantially coplanar with the top surface of said island tops 05 of a subsequent adjacent second row, and a second surface 19 of said fenestrated common base structure 02 in such a first row is coplanar with ones of said undersides 10 of said islands of said subsequent adjacent row; whereas said first and second surfaces are not coplanar with corresponding islands and apertures of a third adjacent row but are rather spaced from them by a distance equal to one of the aforementioned steps. Said stems 07 connecting said base structure 02 with said islands 05 thereby effect the aforementioned stepped profile and provide structural continuity to the whole. Therefore, a first said fastener portion 25 can be attached to a like portion 25 in opposed disposition, or it can be attached to a further portion of itself when doubled or folded into such a position. It is noted that the term "coplanar" as utilized herein is intended as a relative term not intended to preclude twisting or flexing of the whole or any element thereof. A significant aspect of this type of embodiment is that it can be readily produced of virtually any malleable sheet material by the method herein described using a set of cutting/bending dies in a relatively simple apparatus. Such materials may include sheet metal, paper, cardboard, composite materials, thermoformable plastics, or

other sheet materials. Another significant aspect is that this embodiment provides a very low-profile, thus a fully engaged fastener may be only twice the thickness of its base structure. Therefore a wide range of versatile, low- cost, self-aligning, self-attaching, low-profile fastening products is provided which may be utilized for packaging sanitary disposable products and other applications.

A sixth preferred embodiment 29, which is illustrated as the end segments of strap, is shown in Fig. 6. Said embodiment 29 includes a plurality of islands 04 and a plurality of complementary apertures 11 each configured in a chevron configuration on both the first 30 and second 31 sides of common fenestrated base structure 02. Said islands on said first side 30 being configured in a first directional orientation, and said islands on said second side 31 being configured in a second directional orientation; so that the walls 13 of a plurality of said apertures 11 of complementary orientation are defined by said sidewalls 08 of said stem segments 07 and by said undersides 10 of said undercut segments 09 in each of two complementary directional orientations. Therefore, said islands of said first side 30 of said portion 29 may be slidably engaged with apertures of said second side 31 of a similar portion and vice versa, thereby providing a double-sided self-connecting linear fastener.

Fig. 7 illustrates a fastener portion 32 with multi-directional orientation having two opposite engageable sides of similar design. Each such engageable side in this example includes an array of alternately offset islands and apertures of a triangular design similar to that shown in Fig. 2 above. In this embodiment however, said fenestrated common base 02 is contiguous with said stem segments 07 of islands 04 on both said base structure's first 15 and second 19 faces. Said associated aperture openings 12 are accessible to corresponding islands inserted into either surface at 60 degree radial intervals, and may be engaged at such radial intervals. Therefore, embodiments of said type 32, when attached to a like portion (or to a single-sided portion of like design as in Fig. 2) on either surface, provide multi-directional resistance to shear stresses. It is readily apparent that such double-sided, multi-directional fasteners may also incorporate other designs such as the quadrille and hexagonal configurations shown in Figs. 1 and 3.

Fig. 8 illustrates a molded fastener portion, such as that of embodiment type 01 illustrated in Fig. 1, along with a backing portion 34 designed to attach said portion to a substrate material 33 such as fabric. Said fastener portion 01 includes a plurality of receptors 17, each such receptor located at the center of each said stem segment 07 and having an associated receptor entrance 18 located on said second surface 19 of said fenestrated common base structure 02. Backing portion 34 includes a contiguous backing structure 35 having a plurality of attaching pins 36 extending therefrom. Said attaching pins are arrayed in a pattern compatible with said receptors of said fastener portion so that said attaching pins may be inserted through perforations 37 in said substrate material and received through said receptor entrances 18 into said receptors 17, thereby attaching said fastener portion to said substrate. Said attaching pins may be permanently retained in said receptors by friction, or may be held by an adhesive, rf welding or other such known technology.

Said backing structure 35 may be designed to provide sufficient flexibility so as to allow the entire assembly to be flexed if desirable for a particular application. Such flexibility may be useful in many applications such as in apparel. Alternatively, said backing structure 35 may be designed to enhance the rigidity of the complete assembly, thereby reinforcing said fastener portion, or a segment of same at its point of attachment, as in an application where a flexible fastening strap is to be connected to a rigid base.

Corresponding to such requirements for flexibility or rigidity, said backing structure 35 may include fenestrations as illustrated to enhance flexibility or may be solid and contiguous in order to enhance rigidity.

Fig. 9 illustrates an alternative mechanism for attaching a fastener portion 38 to a substrate, wherein said fastener portion is designed to include a plurality of attachment devices 39 extending from said second surface 19 of said base structure. Said attachment devices may be designed in the form of nails 39 as in Fig. 9, rivets 40 as in Fig. 9A, expansion devices 41 as in Fig. 9B, friction fitting devices 47 as seen in Figs. 9C and 9D, Folding devices 49 as in Fig. 9E, or other device appropriate for attachment to a

particular substrate type. Such an attachment device of an appropriate design for a particular substrate may then be attached to same by an appropriate mechanical means such as hammering, peening, expanding, driving, etc.

Fig. 10 schematically illustrates fastener portions 20 which are part of a primary product 42, illustrated as a molded strap. Said product 42 is designed to include said fastener portions as an integral part of said product so that when said product is folded toward itself said first and second portions may be adjustably fastened. Said product may include a first portion 44 configured in an upward facing arrangement, and a second portion 45 configured in a downward facing arrangement as illustrated, or may comprise both fastener portions configured in like arrangements. Said product 42 may also optionally comprise a component having a third portion spaced from a fourth portion, wherein the first portion 44 is contained in said third portion and the second portion 45 is contained in said fourth portion. Said product 42 may include an optional elastic segment 46, designed to allow said second part 45 to be stretched prior to fastening so as to provide said relative shearing force as needed to slidably engage the portions by the inherent elasticity of said resilient segment. It is important to note that virtually any type of improved slidably engageable fastener may be readily substituted in a product in lieu of the triangular design illustrated. Likewise, it should be noted that a slidably engageable fastener portion may be integrally molded or formed as part of a wide variety of primary products or components, and that such fastener portions may be utilized for component assembly or as a functional sub-part of such a product or component.

A Method for producing Improved Slidably Engageable Fastening Devices of various types includes the provision of a set of interengaging dies and an apparatus for engaging such dies in order to cause a material inserted or injected into a cavity provided by such dies to take the desired form of such fastening device, as further described below. Fig. 11 schematically illustrates a portion of such a set of dies designed to produce a molded fastener portion of the type 01 shown in Fig. 1, however it should be emphasized that the subject method may be applied to improved fastener embodiments of any type in a wide range of materials.

With reference to Fig. 11, a first die 101 comprises a plurality of cavities 103 and includes surface segments 104 which are cavity walls, and other surface segments 105 which provide gates defining fenestrations 03 in the resultant product 01. A second die 102 also comprises said plurality of cavities 103 and includes surface segments 107 which also are cavity walls, other surface segments 108 providing gates, and also includes surface segments 111 which are cavity walls defining the undersides 10 of the resultant product 01. Said gates 105 include a contact surface which is designed to engage with a contact region of said gates 108 when said first and second dies are intermeshed so as to define fenestrations 03, wherein ones of such fenestrations are at least partially aligned with ones of undersides 10 of said product in a direction perpendicular to base structure 02. When said first and second dies are engaged by an appropriate apparatus, said cavities 103 are interconnected so as to define the common fenestrated base structure 02 of said product as well as integral stems, islands and surface features. Said first and second dies may also typically include a perimeter gate and other aspects necessary for production known to industry which are not herein claimed.

It can be appreciated from Fig. 11 that said cavities 103 include cross sections which are contiguous and other cross sections which are not contiguous. Said gates 105, 108 are designed to engage each other so as to effect interfacing gates of a first type 112 which are substantially parallel to the molding axis (that is, perpendicular to the interfacing plane of each said die). Typically the walls of said gates of this first type are slightly inclined relative to the molding axis to allow molds to release without lockup. When said first and second dies are engaged, certain of such gates of the first type 112 effectively define a second cavity 106 which is located within the somewhat larger first cavity 103 occurring when said first and second molds are not engaged. In addition, said surface segments 105, 108 may also be designed to engage each other in a juxtaposition which is substantially perpendicular to the molding axis so as to effect interfacing gates of a second type 113, thereby precisely defining the depth of said cavity 103 and therefore defining the thickness of said base structure 02 and the associated structure. Said cavity

103 may be filled with a thermoplastic resin or other moldable material so as to provide a molded product, using technology known to industry.

Referring back to Fig. 1, it should be noted that said fenestrated base structure 02 of said product 01, as defined by said cavity 103, includes fenestrations that align, in a direction generally perpendicular to said fenestrated base structure, with said undersides 10 and also include additional fenestrated areas 114 which do not align in such direction with said undersides. Such additional fenestrated areas allow a product to be designed to provide maximum economy of material and to enhance the flexibility of said product as may be desired for certain applications. Said additional fenestrated areas 114 also allow said dies to include interfacing gates of type 113 as described above, so as to precisely control the relative thickness of said product. Said additional fenestrated areas 114 may also be incorporated to enhance function by receiving the conical protrusions 14 of corresponding islands, to provide means for attachment (as by sewing), to provide aesthetic effect, or to otherwise enhance said product.

An apparatus of diverse generic types, as schematically illustrated in Figs. 15-18, is provided to align, interengage, and pressurize said first and second dies 101, 102. When said first and second dies are caused to align and interengage by such an apparatus, said cavity 103 is provided having sidewalls which generally coincide with the surface of the desired product (such as 01). When a flowable or malleable substance is inserted between said first and second dies, said apparatus causes pressure to be exerted on such substance within said cavity so that such substance is forced to take the general form of said cavity 103, thereby providing said product. Such substance may be a moldable material such as thermoplastic resin or fibrous slurry. Alternatively, when the product is of a design that includes a generally consistent thickness, said substance may be a malleable material such as sheet metal, formable plastic, paper, composite material, or paperboard. In the former instance, said moldable substance is generally injected under pressure and is intended to completely fill said cavity 103. In the latter instance, said malleable material is intended to take the approximate shape of said cavity 103 but does not necessarily fill said cavity completely.

Fig. 12 illustrates a set of dies designed to produce a directionally oriented slidingly engagable fastener of the stepped type 25 as seen in Fig. 5 above. A first die 101 includes cavities 103, cavity walls 104, and surface segments which define perforations 105. A second die 102 includes cavities 103, cavity walls 107, and other surface segments which define perforations 108. Said first and second dies may be included in an apparatus designed for molding so that said cavities 103 may be filled with a moldable substance to provide a fastener portion 25, as in the previous example. Alternatively, it will be noted that said Slidingly Engagable Fastener Portion 25 as well as other embodiment types are of a design which can also be produced by forming a malleable sheet material such as paper or sheet metal, depending only on the general type of apparatus chosen and specific design of said dies as to hardness, scale, etc. Where the subject method is utilized to form a product of a such malleable materials, at least one of said first and second dies generally includes a plurality of punching segments each having a punching surface and a plurality of edge segments having cutting edges 122 and the other of said dies generally includes edge segments providing complementary anvils 123. It should be noted that the subject method used to produce such "formed" fastening portions has significant utility, providing on one hand an inexpensive means of producing relatively strong sheet metal fasteners for use in construction and industry, and on the other hand a range of inexpensive fiber, paper, or biodegradable fasteners for disposable sanitary products, packaging and temporary assembly.

Optionally, one of said first and second dies may also include a plurality of ejection slots 115, each said ejection slots being aligned with a secondary punching segment 116 of the other of said first or second dies, which surface segment is intended to punch through said malleable material so as to eject a part thereof, thereby providing said additional perforated areas 114 as otherwise described above in a molded product. It should be noted that when producing a formed fastener product of a sheet material as in this instance, dies having said interfacing gates of the second type 113 as described above are unnecessary, in that the thickness of material is generally predetermined.

Fig. 13 schematically illustrates a set of said first and second dies as described above which also include aspects defining a another primary product 125 of which two of said

fastener portions are an integral part. In this example said primary product might be an elongated plastic strap similar to the embodiment 43 of Fig. 11 (but having fastener portions comprising a quadrille configuration as in embodiment 01) having complementary fastener portions at each end which in this instance are configured in opposing directions and oriented to opposite sides of said product so that one end of the resultant said strap may be adjustably attached to the other. Said interconnected cavities 103 are also interconnected to a primary cavity 126, which defines said product 125. It is important to note that virtually any formable or moldable primary product or component could likewise incorporate a fastener portion as a subsidiary portion of the whole by incorporating a set of dies as herein described as subparts of the dies used to produce such primary product or component.

Fig. 14 schematically illustrates how the subject method may also be utilized to produce double-sided fasteners such as that of type 32 of Fig. 7 above. A set of said first and second dies 101,102 are substantially identical, each having cavities 103, cavity walls 104,107, interfacing gates 105,108 and walls defining undersides 111. Each said die therefore simultaneously defines both a first (upper) basal surface 15 of a fastener with associated islands 04 extending therefrom, and a second (under) basal surface 19 as well as the island undersides 10 of a fastener on a second side of said double-sided fastener.

In each type of apparatus 117 as described herein, said first and second dies also include other aspects common to industry including means for causing properly registered alignment, means for extracting extraneous material, means for ejecting products, means for heating and cooling, and other aspects common to industrial molding and die forming processes which are not claimed as part of the present invention.

As illustrated schematically in Fig. 15 an apparatus 117, being a simple reciprocating injection molding machine, is provided to first align and intermesh a set of said first and second dies 101, 102 by a known means for providing sequential pressure 139, and to secondly inject a moldable substance 128 into said interconnected cavities 103 by a known means for injecting such a substance under pressure. Said first and second dies may also include known means for introducing and distributing said substance, ejecting

air, cooling, and ejecting said product. After said substance is sufficiently hardened, said first and second dies are disengaged by said reciprocating apparatus and said product is ejected by same.

A reciprocating cutting/forming press apparatus 117 is illustrated in Fig. 16. Herein said first 101 and second 102 dies are aligned and intermeshed under pressure so as to form a product 118 out of a malleable sheet material 131 such as sheet metal, paper, or formable plastic. In this instance, one of said first and second dies includes surface segments having a plurality of cutting edges 122 and the other of said first and second dies includes surface segments having a plurality of anvil portions 123 so that said product includes a plurality of cut edges 124, at least some of said cut edges being adjacent to said undersides 10 of said product, and at least some others of said cut edges being adjacent to said perforations 03. Such an apparatus, and said dies may also include means for ejecting excess material such as the ejection slots 115 illustrated in Fig. 12. Said reciprocating press may include mechanisms to assure alignment, provide sequential application of pressure, provide for sequential movement of product, as well as other aspects known to the forming industry. Such a reciprocating cutting/forming press may be designed to provide a sequential (row by row) forming operation as schematically illustrated here or to provide multiple row forming of relatively larger fastener sheets, depending on material used and design criteria. Material may be supplied into such an apparatus or other forming apparatus as individual sheets 131 or from a coil 131'.

Fig. 17 schematically illustrates a rotating cutting/forming press apparatus 117 having pluralities of said first and second dies 101, 102 arrayed on the surfaces of a set of counter-rotating rollers 129, 130 so that, as a malleable sheet material 131 is inserted between said rollers, it will be continuously formed into a continuous length of fastener product 132. Said malleable material 131 may be provided sequentially in sheet form or continuously in a coil form 131' as illustrated. Said product 132 is then extruded from said rollers in a continuing fashion and may be cut into useable sizes or otherwise modified by subsequent processes known to industry.

A continuous molding apparatus 117 is schematically illustrated in Fig. 18, wherein said first and second dies 101, 102 are arrayed on the surfaces of a set of rotating molds 133, 134. A flowable molding substance 128 such as thermoplastic resin is inserted through a nip 135 under sufficient pressure to completely fill interconnected cavities 103 as defined by said interengaging dies. Said apparatus includes means for cooling said material as is common to the industry so that said product 110 may be sequentially stripped from the molds as it hardens. An important aspect of such an apparatus is that said interfacing gates of the parallel type 113 serve to define the relative disposition of said first and second molds 133, 134 thereby precisely defining the thickness of said fenestrated base structure 02 as well as individual elements of said product.

At least one of said rotating molds 133, 134 may optionally be provided in the form of a continuous molding belt 135. This option may be included in order to expedite the production process by providing a longer mold contact time for cooling prior to product ejection, thereby allowing said rotating molds to operate at a faster speed.

Optionally, a fabric or other reinforcing material 48 may be integrally molded into said product for the purpose of reinforcing, providing selvage for sewing, or other purpose. Said reinforcing material 48 is temporarily adhered to the peripheral surface of one of said first or second counter rotating molds 133 so that said material is caused to pass through said apparatus as said moldable substance 128 fills said interconnected cavities 103, thence becoming integrally molded with said product. Such a reinforcing material 48 which has perforations which can align with protruding elements of said first or second dies 102 can be caused to substantially attach to said protruding elements prior to the introduction of said substance 128, thereby aligning and registering said substrate 136 with said interconnected cavities 103 between said perforations 109.

It is to be understood that the forgoing description and associated drawings are intended to schematically demonstrate a wide range of embodiments which may be produced by the method described or by other methods. It is the intent of these documents to describe a range of variations which may be modified or combined in diverse ways within the scope of this invention. It is further intended that all matters contained in the foregoing